



# QUICK CODE ACCESS



Heavy duty locks with on the door code change capabilities. Simple and quick control of coded access.

Traditionally, changing the code on a mechanical lock requires the lock to be removed from the door; the CL600 however, features QuickCode functionality allowing on the door code changes in seconds. The CL600 QuickCode brings significant advantages to commercial users such as hospitals, schools and local authorities. The locks allow for various ways of managing entry by code, key or code free access via full size lever handles.



Easy to  
install



On the door  
code changes



Limited lifetime  
guarantee\*

**8,191**

Total code  
combinations

## FEATURES

- Full size lever handles with return to door
- Suitable for wooden doors between 35mm - 60mm thick
- PVD low maintenance finish
- Code Free access options
- Suitable for internal and external use
- Mortice latch and mortice lock models available
- Large three coil lever return spring suitable for high traffic use
- Available in a brushed steel finish
- Codelocks Fire Kit Packs can be fitted to latch locks for 30 or 60 minute fire doors. Tested in accordance with BS EN 1634-1

## LOCK MODELS



CL600

### Front and Back Plates

Front and back plates only. Use with existing mortice latch or lock. Existing lock must have a fixing hole 22mm (7/8") below follower (spindle).



CL610 / CL615

### Mortice Latch


Medium duty tubular mortice latch with 'anti-shim' plunger. Latch retracts by turning inside handle freely, or the outside handle after code input.



CL610 / CL615 BB

### Back to Back Option (BB)

Medium duty tubular mortice latch. Two coded plates for installation on both sides of the door. Provides coded access in both directions.




CL620


### Mortice Lock

Euro profile mortice sash lock with deadbolt and latchbolt. With the deadbolt thrown it denies access to code users. Supplied with Euro profile cylinder and three keys.

### Two Mortice Latch Sizes Available:



Requires 25mm x 82mm (1" x 3 1/4") hole



Requires 25mm x 92mm (1" x 3 5/8") hole

## ADDITIONAL FEATURES

### Code Free Access

The CL615 models provide a Code Free option. The outside lever will retract the latch freely until disabled.

### Panic Kit Option

An extra long spindle is provided to work with most single point panic pads or bars.

### Split Follower

The CL620 Mortice Lock model utilises a split follower as a safety feature. This enables the inside lever to retract the deadbolt and latchbolt, after the deadbolt has been thrown, to prevent an accidental lock in.

### Marine Grade

Selected CL600 models are also available in a black, marine grade finish. Salt spray test up to 1000 hours\*

\*Tested in-house by Codelocks



## TECHNICAL SPECIFICATIONS

### Code Change Method

QuickCode allows on the door code changes in seconds!

FEATURE	DESCRIPTION
Spindle Type	Two part 8mm (5/16") spring loaded spindle
Mortice Latch	Medium duty latch with 'anti-shim' plunger
Mortice Lock	Euro profile mortice sash with deadbolt and latchbolt
Material	Zinc Alloy
Finish	PVD (Physical Vapour Deposition), low maintenance
Finish Colour	Brushed Steel
Non Handed	Locks will fit doors hung on the left or right
Door Thickness	35mm - 60mm (1 3/8" - 2 3/8")
Key Override	As standard
Keyed Alike	Locks can be supplied keyed alike on request
Key Cylinder Change	As standard
Code Storage	Single Code
Fitting Options	Vertical only
Suitable For	Internal and external use
Standards	Codelocks Fire Kits can be fitted to latch locks for 30 or 60 minute fire doors. Tested in accordance with: BS EN 1634-1

## PRODUCT DIMENSIONS

CL600 CL610 CL615

CL620

