

# ANTI-VANDAL MECHANICAL KITLOCK



Simple, tough and good value for money, the KL15 offers mechanical keyless access with Private or Public Function models suitable for a variety of locker and cabinet applications.

The KL15 can be surface mounted with an ergonomically designed surface trim plate that provides additional grip allowing ease of opening. If it's a sleek look that will better suit the application, the KL15 can also be flush fitted.



Easy to install



Mechanical keyless access



One year guarantee\*



Private and Public Functions

## FEATURES

- Code retrieval function
- Flush or surface mounted
- Anti-vandal handle
- Salt spray tested
- High / low temperature tested
- High / low humidity tested
- 4 wheel combination
- Up to 10,000 unique combinations
- Locked / unlocked indicators
- Private and Public Function
- Suitable for internal and external applications

## FUNCTIONS



### Private Function

The KL15 Private Function is ideal for use where the same, personal 4 digit code will be repeatedly used, e.g. an employee with the same locker/drawer in the workplace.



### Public Function

The KL15 Public Function is ideal for short term, multiple occupancy applications. The user enters a personal four digit code, this locks the lock. The same code is entered once only to open the lock, the lock remains open ready for the next user.



### Code Retrieval

Use the Master Key to retrieve the forgotten code by simply turning the dials individually until the correct code 'clicks' into place.



### Installation

The KL15 can be installed to fit either flush or surface mounted applications. All necessary fixings are supplied with the lock.



## TECHNICAL SPECIFICATIONS

FEATURE	DESCRIPTION
Functions	Private or Public Function
Code Length	4 digit
Code Storage	Single code
Suitable For	Internal and external applications
Surface Mount	Fixed spindle suitable for panel thickness 0.8mm - 18mm ( $\frac{1}{32}$ " - $\frac{11}{16}$ " )
Flush Fit	Suitable for panel thickness 0.8mm - 36mm ( $\frac{1}{32}$ " - $1\frac{3}{8}$ " )
Handing	Vertical, right hand and left hand
Indicators	Locked (red) / unlocked (green)
Fixings	All surface mount and flush fit fixings supplied as standard
Cam	Flat and cranked cam supplied as standard

## PRODUCT DIMENSIONS

